# **RELIEF VALVES** H900 SERIES







### **RELIEF VALVES H900 SERIES**

#### FEATURES

- 316St.St. Construction
- Service 10-225 psi

GENERAL


- One spring for all set pressure range
- Available in all pipe threads and LET-LOK<sup>®</sup> connectors
- Sizes: 1/4" or 6mm

The H900 series is a relief valves for low pressure service. The valve is normally closed. It will open when system pressure reaches the set level. It will re-close when the system pressure falls below the set level.

H900 - MATERIALS								
ltem No.	Components	Qty.	Valve Body Material					
1	Cap Plug	1	Polypropylene					
2	Adjustment Cap	1	St.St. 316					
3	Cap Lable	1	Polyester					
4	Spring	1	St.St. 302					
5	Locking Nut	1	St.St. 316					
6	Spring Support Disc	1	St.St. 316					
7	Bonnet	1	St.St. 316					
8	O-ring	1	Viton <sup>®</sup> (Fluorocarbon)					
9	Stem	1	St.St. 316					
10	O-ring	1	Viton <sup>®</sup> (Fluorocarbon)					
11	Retaining Ring	1	PH1-57 Mo					
12	Poppet	1	St.St. 316					
13	Seal	1	Viton <sup>®</sup> (Fluorocarbon)					
14	Insert	1	St.St. 316					
15	Packing	1	PTFE					
16	Ring	1	St.St. 316					
17	Body	1	St.St. 316					

## DIMENSIONS

Description	Connection / size		Dimensions mm:				
	inlet	outlet	Н	N	S	L	
H900	1/4 LET-LOK®	1/4 LET-LOK®	37	39	50	105	
H900	6MM LET-LOK®	6MM LET-LOK®	37	39	50	105	
H985	1/4 Male NPT	1/4 Female NPT	32	30	40	100	
H995	1/4 Male NPT	1/4 LET-LOK®	32	39	50	100	






#### CLEANING AND PACKAGING

HAM-LET's H900 Relief Valve is treated with the HAM-LET Passivation Cleaning and Packaging (Procedure 8075).

Oxygen Cleaning and Packaging (Procedure 8055) is available as an option.

#### TESTING

The HAM-LET H900 Relief Valve designs have been tested for Proof and Burst. Every H900 Relief Valve is factory tested for proper set and resealing preformance.



Select the right component for safety's sake: The total design of the system must be taken into consideration when selecting components in order to ensure that your Ham-Let products provide safe, trouble-free operation. It is the responsibility of the system designer and the user to consider the compatibility of the materials, of the components and system, the function of the component, appropriate ratings and to ensure proper installation, operation and maintenance.

Improper selection or use of products can cause property damage or personal injury, in respect of which the system designer and/or the user shall be solely liable and responsible.

